

# ORDER FORM

A4 (210x297)

Type of Bushing:

DIN

EN

LMT [(0,0) (196,286)]

System Rated Voltage (kV):

12

24

36

52

.DWG

Rated Current (A):

250   
(Only for 52kV)

630   
(Only for 52kV)

1250

2000

3150

FILE = 3930

Creepage distance:

..... mm

OR

..... mm/kV

OR

..... Pollution level IEC 60815  
(b;c;d;e / 1;2;3;4)

Airside components:

Naked

Nuts

DIN Flag

UNEL Flag

NEMA Flag

SPECIAL



Oil side components:

Style C0

Style C6

Style E1

Style T1

Style A1  
(Flag .....)

SPECIAL

REV. 03 DTD 23/08/21

Gasket:

NBR  
(-30°C/+120°C)

NBC (Cork TD1120)  
(-30°C/+120°C)

Low temp.  
(Cork TD7000)  
(-45°C/+120°C)

Very Low temp.  
(Blue Fl/Sil)  
(-60°C/+150°C)

Heavy Duty  
(VITON)  
(-20°C/+150°C)

Surface finishing:

Tinplated 6/10 µm

Silver plated 6/10 µm

Only Flag (F)

Flag & Cap (F+C)

Flag/Cap/Rod (F+C+R)

CT accomodation:

CT150

CT300

CT500

SPECIAL  
C0=.....



Arcing horns:

NO

YES (DIN STYLE)

YES (UNEL STYLE)

Type of Fixation Flange:

DIN

EN

Material of fixation Flange:

Aluminium

Stainless steel

Notes:

.....  
.....  
.....



Titolo

MV Bushing  
Order sheet

Data 30/01/14

Scala ==

Dis.

Visto

Dis. Nr

3930

1	2	3			
---	---	---	--	--	--

MR si riserva a termini di legge la proprietà del presente disegno con divieto di riproduzione o comunicarlo a terzi senza sua autorizzazione.