

ORDER FORM

System Rated Voltage (kV):

12 24 36 52

Rated Current (A):

630 1250 2000 3150 4500
 Flange type B Flange type C Flange type D Flange type D Flange type D
 (For 52kV : D) (For 52kV : D) (For 52kV : D) (Only for 12;24;36Kv)

Creepage distance:

..... mm OR mm/kV

Airside components:

Nuts (Only for 630A) DIN Flag UNEL Flag NEMA Flag SPECIAL

Oil side components:

Style C0 Style C6 Style E1 Style A1 (Flag) SPECIAL

Gasket:

NBR (-30°C/+120°C) NBC (Cork TD1120) (-30°C/+120°C) Low temp. (Cork TD7000) (-45°C/+120°C) Very Low temp. (Blue FI/Sil) (-60°C/+150°C) Heavy Duty (VITON) (-20°C/+150°C)

Surface finishing:

Tinplated 6/10 µm Silver plated 6/10 µm
 Only Flag (F) Flag & Cap (F+C) Flag/Cap/Rod (F+C+R)

CT accomodation:

CT150 CT300 CT500 SPECIAL CO=.....

Notes:

.....



DATE	NAME	DOCUMENT NO.			
DFTR:05/12/17	A.GIORGI				
CHKD:05/12/17	A.GIORGI	CHANGE NO.	SCALE		
STAND:05/12/17	A.GIORGI	03			

DIMENSION
 IN mm
 EXCEPT AS
 NOTED



COMPOSITE BUSHING ORDER SHEET

SERIAL NUMBER	
MATERIAL NUMBER	SHEET /

CEDASPE S.p.A. COPYRIGHT RESERVED
 THE REPRODUCTION, DISTRIBUTION AND UTILIZATION OF THIS DOCUMENT AS WELL AS THE COMMUNICATION OF ITS CONTENTS TO OTHERS WITHOUT EXPRESS AUTHORIZATION IS PROHIBITED. OFFENDERS WILL BE HELD LIABLE FOR THE PAYMENT OF DAMAGES. ALL RIGHTS RESERVED IN THE EVENT OF THE GRANT OF A PATENT, UTILITY MODEL OR DESIGN.