

# ORDER FORM

System Rated Voltage (kV):

12

24

36

52

Rated Current (A):

630

1250

2000

3150

4500   
(Only for 12;24;36kV)

Creepage distance:

..... mm                      OR                      ..... mm/kV

Airside components:

Nuts  
(Only for 630A)

DIN Flag

UNEL Flag

NEMA Flag

SPECIAL

Oil side components:

Style C0

Style C6

Style E1

Style A1  
(Flag .....)

SPECIAL

Gasket:

NBR  
(-30°C/+120°C)

NBC (Cork TD1120)  
(-30°C/+120°C)

Low temp.  
(Cork TD7000)  
(-45°C/+120°C)

Very Low temp.  
(Blue Fl/Sil)  
(-60°C/+150°C)

Heavy Duty  
(VITON)  
(-20°C/+150°C)

Surface finishing:

Tinplated 6/10 μm

Silver plated 6/10 μm

Only Flag (F)

Flag & Cap (F+C)

Flag/Cap/Rod (F+C+R)

CT accomodation:

CT150

CT300

CT500

SPECIAL  
C0=.....

Notes:

.....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....



Titolo  
**Composite Bushings  
SBC Order sheet**

Data 05/12/17

Scala ==

Dis.

Visto

Dis. Nr  
**4404**

1				
---	--	--	--	--

FILE = 4404 .DWG LMT [(0,0) (196,286)] A4 (210x297)  
 REV. 01 DTD 23/08/21  
 MR si riserva a termini di legge la proprietà del presente disegno con divieto di riproduzione o comunicarlo a terzi senza sua autorizzazione.