Technical data
CAPT® 040+. De-energized tap-changer

13686366/00 EN



© Reinhausen GmbH
Dissemination and reproduction of this document and use and disclosure of its content are strictly prohibited unless expressly permitted.
Infringements will result in liability for compensation. All rights reserved in the event of the granting of patents, utility models or designs.
The product may have been altered since this document was published.
We reserve the right to change the technical data, design and scope of supply.
Generally the information provided and agreements made when processing the individual quotations and orders are binding.
The product is delivered in accordance with MR's technical specifications, which are based on information provided by the customer. The customer has a duty of care to ensure the compatibility of the specified product with the customer's planned scope of application.
The original operating instructions were written in German.

Table of contents

1 Introduction 4
1.1 Function description 4
1.2 Switching concept 4
1.3 De-energized tap-changer IDs 4
..... 000
..... 000

2 Technical data 8
2.1 Insulating fluid 8
2.2 Temperature range 8
2.3 Permitted voltage stresses 8
2.4 Rated through-current 9

3 Drawings 10
3.1 10195810 11
3.2 10195793 12
3.3 10195811 13
3.4 10195812 14
3.5 10195814 15
3.6 10195815 16
3.7 10195816 17
3.8 10195817 18
3.9 10195818 19
3.10 10195819 20
3.11 10195820 21
3.12 10195821 22
3.13 10195822 23
3.14 10195829 24
3.15 10195830 25
3.16 10195833 26
3.17 10195834 27
3.18 10195835 28
3.19 10195836 29
3.20 10195837 30
3.21 10195838 31
3.22 10195839 32
3.23 10195840 33
3.24 10195841 34
3.25 10195842 35
3.26 10195843 36
3.27 10195844 37
3.28 10195845 38
3.29 10195846 39
3.30 10195852 40
3.31 10195853 41
3.32 10197367 42
3.33 10195854 43
3.34 10195856 44
3.35 10195857 45
3.36 10195858 46
3.37 10195859 47
3.38 10195861 48
3.39 10195862 49
3.40 10195863 50
3.41 10195864 51
3.42 10195865 52
3.43 10195866 53
3.44 10195867 54
3.45 10195868 55
3.46 10195869 56
3.47 10195870 57
3.48 10195871 58
3.49 10195872 59
3.50 10195873 60
3.51 10195874 61
3.52 10195875 62
3.53 10195876 63
3.54 10195877 64
3.55 10195878 65
3.56 10195879 66

1 Introduction

This technical file contains detailed information about the technical properties of the product.

1.1 Function description

De-energized tap-changers are used for setting the voltage of oil-immersed transformers. In contrast to on-load tap-changers, the required winding taps must be set with the transformer switched off on the high-voltage and low-voltage side.

The de-energized tap-changer is changed over from one operating position to the next by rotating a drive shaft. The de-energized tap-changer is actuated using a motor-drive unit or manual drive.

1.2 Switching concept

The design of the de-energized tap-changer is based on a modular system that enables a product range for the following basic connections:

- Linear de-energized tap-changer
- Double-linear de-energized tap-changer
- Bridging de-energized tap-changer
- Double-bridging de-energized tap-changer
- Exclusion of turns de-energized tap-changer
- Series-parallel de-energized tap-changer
- Star-delta de-energized tap-changer
- De-energized tap-changer for special applications

1.3 De-energized tap-changer IDs

This technical document contains standard applications and standard configurations. The following table explains the IDs for the different de-energized tap-changer types.

> **i** For special versions of the de-energized tap-changer (de-energized tap-changer with multiple stages, mirror-image mounting, special connections, etc.), a technical analysis is required. Contact Reinhausen GmbH for more information.

Example of a de-energized tap-changer designation: B02MFS-M0314-3M1-AN2ANS

	Meaning	Version	Possible parameters
B	Type	Bridging contact scheme	B
		Linear contact scheme	L
02	Highest voltage for equipment Um	26 kV	02
		36 kV	03
		52 kV	05
		73 kV	07
M	Max. rated through-current	1000 A	K

	Meaning	Version	Possible parameters
M	Max. rated through-current	1600 A	M
F	Contact type	Threaded	T
		Flat	F
S	Surface treatment	Silver-plated contacts	S
M	Number of moving contacts per contact group (stage)[1]	1	M
		2	B
		3	T
03	Number of maximum operating positions[4]	2...15	02...15
14	Contact clearance	70 mm	07
		100 mm	10
		140 mm	14
		210 mm	21
		280 mm	28
3	Number of contact planes (decks)[2]	1	1
		2	2
		3	3
		4	4
M	Number of contact groups (stages) per contact plane (deck)[3]	1	M
		2	B
		3	T
		4	Q
		5	P
		6	H
		2+1	F
1	Number of de-energized tap-changer columns[3]	1	1
		2	2
		3	3
A	Materials	Phenolic resin paper rods and steel components	A
		Phenolic resin paper rods and stainless steel components	B
		Epoxy resin fiberglass rods and steel components	C
		Epoxy resin fiberglass rods and stainless steel components	D
N	Equipotential rings	Without equipotential rings[5]	N
		Equipotential rings	A
		Equipotential rings and insulating shield	C
2	Gear unit position[3]	1	1

	Meaning	Version	Possible parameters
2	Gear unit position[3]	2	2
		3	3
		4	4
		5	5
		6	6
		7	7
A	Output shaft[2]	Direct	A
		Bevel gear 0°	B
		Bevel gear 90°	C
		Bevel gear 180°	D
		Bevel gear 270°	E
N	Additional bracket	No additional information	N
		Additional bracket on de-energized tap-changer	A
		Additional bracket on de-energized tap-changer and fastenings	B
S	Version	Standard	S
		Special	X

[1] With appropriate product configuration, the number of moving contacts per contact step (stage) can be up to 6 contacts (special configuration required)

[2] For a detailed description of the parameters, see [▶10195853]

[3] For a detailed description of the parameters, see [▶10195852]

[4] The maximum number of operating positions is recalculated based on the distance between the fixed contacts

[5] For the 73 kV voltage class, equipotential rings are always supplied where the clearance between the fixed contacts is between 210 mm and 280 mm

Example of a designation for a drive layout: 070-040+.LAYOUT2A.S-DP

	Meaning	Version	Possible parameters
070-040+	Drive series	Drive for de-energized tap-changer	070-040+
2A	Layout type[6]	1A	1A
		1B	1B
		1C	1C
		2A	2A
		2B	2B
		2C	2C
		2D	2D

	Meaning	Version	Possible parameters
2A	Layout type[6]	2E	2E
		3A	3A
		3B	3B
		3C	3C
		3D	3D
		3E	3E
		4A	4A
		4B	4B
		4C	4C
		5 A	5 A
		5B	5B
		5C	5C
		5D	5D
S	Drive shaft	Metal shaft	S
		Insulating shaft	FL
D	Surface treatment	Without	n/a
		Geomet ®[7]	D
P	Accessories	Without	n/a
		Stainless steel protective tube[8]	P

[6] All layout types are also available as a mirror image of the standard version. These versions are identified by the layout type designation followed by "I" (for example, 1AI). For detailed information, see

[7] Only applicable to these layout types and their mirror-image versions:
- 4A
- 4B
- 4C
- 5 A
- 5B
- 5C
- 5D

[8] Stainless steel protective tubes are included as standard for versions with motor-drive unit. For versions with manual drive, protective tubes are only available as an option for the following layout types and their mirror-image versions:
- 4A
- 4B
- 4C
- 5 A
- 5B
- 5C
- 5D

2 Technical data

2.1 Insulating fluid

The following insulating fluids are suitable for use with this de-energized tap-changer:

Insulating fluid	– Unused insulating oils derived from petroleum products[1)] in accordance with IEC 60296 and ASTM D3487 (equivalent standards on request) – Unused insulating oils derived from other virgin hydrocarbons in accordance with IEC 60296, or blends of these oils with petroleum products[1)] in accordance with IEC 60296, ASTM D3487 or equivalent standards on request – Alternative insulating fluids, such as natural and synthetic esters or silicone oils, on request [1)] Gas-to-liquid oils (GTL oils) are understood in this context to be petroleum products

Table 1: Insulating fluid

> Contact Reinhausen GmbH for applications with other types of insulating fluids (silicone or ester).

2.2 Temperature range

You can operate the de-energized tap-changer in the rated load range at oil temperatures of -40 °C to +105 °C and in accordance with IEC 60214-1 up to +115 °C (during emergency transformer operation in accordance with IEC 60076-7).

> Depending on the version, you can operate the de-energized tap-changer at temperatures ranging from -60 °C or to +155 °C[1)], if required. When doing so, there may be limitations regarding the seals. In this case, contact Reinhausen GmbH.

[1)]In accordance with IEC 60085:2007 Class F

2.3 Permitted voltage stresses

The maximum permissible operating voltage to ground, between the phases and between adjacent contacts of the de-energized tap-changer corresponds to half the value of the rated short-duration power frequency withstand voltages listed in the following tables.

The insulating performance of the de-energized tap-changer insulation is determined by rated withstand voltages (following tables) that correspond to the grades required in practice. Stress on the internal de-energized tap-changer insulation mainly occurs during the impulse voltage test and during the induced voltage test of the transformer. It also depends on the position of the de-energized tap-changer.

Um [kV]	Insulation distance	LI	LIC	AV
26	To ground and between the phases	150	165	50
36	To ground and between the phases	200	220	70
52	To ground and between the phases	250	275	95
73	To ground and between the phases	350	385	140

Type	Insulation distance	Uir	LI	AV
Bridging contact / linear contact	Between adjacent contacts – contact clearance 70 mm	20	130	40
	Between adjacent contacts – contact clearance 100 mm	25	170	50
	Between adjacent contacts – contact clearance 140 mm	31	200	60
	Between adjacent contacts – contact clearance 210 mm	52	280	100
	Between adjacent contacts – contact clearance 280 mm	57	330	110
Linear contact	Between tap and common contacts	31	200	60

Abbreviations for the rated insulation level:

LI	Full wave lightning impulse (kV, 1.2/50 µs)
LIC	Chopped wave lightning impulse (kV, 1.2/50/3 µs)
AV	Applied voltage (kV, 50 Hz, 1 min)
Uir	Rated step voltage (kV)


2.4 Rated through-current

The de-energized tap-changer is available in two rated through-current classes.
- 1,000 A
- 1,600 A


Both classes are available either with flat or threaded fixed contacts.

3 Drawings


LINEAR
DE-ENERGIZED TAP-CHANGER




DOUBLE-LINEAR
DE-ENERGIZED TAP-CHANGER




BRIDGING
DE-ENERGIZED TAP-CHANGER




DOUBLE-BRIDGING
DE-ENERGIZED TAP-CHANGER




EXCLUSION OF TURNS
DE-ENERGIZED TAP-CHANGER



SERIES-PARALLEL
DE-ENERGIZED TAP-CHANGER



STAR-DELTA
DE-ENERGIZED TAP-CHANGER



SPECIAL CONNECTION
DE-ENERGIZED TAP-CHANGER ARE ALSO POSSIBLE

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.	
Dftr.	25.06.2026	CRESTANIN	SED 13170037 000 00	Scale -
Chkd.	25.06.2026	MONDINN	Change no. 1143366	
Stand.	25.06.2026	CRESTANIN		


Projection method


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
040+ Connection diagrams
Basic connection in simplified form

SERIAL NUMBER –
MATERIAL NUMBER 101958100E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)					
		A	B1	C	D	G	P
26	2	1140	460	140	179	141	70
	2	1320	520	200	179	141	100
	2	1560	600	280	179	141	140
	3	1350	530	210	179	141	70
	3	1620	620	300	179	141	100
	4	1560	600	280	179	141	70
	5	1770	670	350	179	141	70

U_m (kV)	N° Positions	Dimensions (mm)					
		A	B1	C	D	G	P
36	2	1271	525,5	140	212	173,5	70
	2	1451	585,5	200	212	173,5	100
	2	1691	665,5	280	212	173,5	140
	3	1481	595,5	210	212	173,5	70
	3	1751	685,5	300	212	173,5	100
	4	1691	665,5	280	212	173,5	70

U_m (kV)	N° Positions	Dimensions (mm)					
		A	B1	C	D	G	P
52	2	1496	638	140	268	230	70
	2	1676	698	200	268	230	100
	3	1706	708	210	268	230	70

U_m (kV)	N° Positions	Dimensions (mm)					
		A	B1	C	D	G	P
73	2	1831	805,5	140	352	313,5	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12326679 000 00	Scale 1:10	
Chkd.	19.06.2026	MONDINN	Change no. 1143366		
Stand.	25.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED

MR


DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 26 kV, 36 kV, 52 kV, 73 kV
– for bridge connection–


SERIAL NUMBER –


MATERIAL NUMBER 101957930E

SHEET 1 / 1

A3







U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	B2	C	D	G	P
26	2	2224	740	702	420	179	141	210
	2	2644	880	842	560	179	141	280
	3	2224	740	702	420	179	141	140
	3	2854	950	912	630	179	141	210
	4	2164	720	682	400	179	141	100
	4	2644	880	842	560	179	141	140
	5	2464	820	782	500	179	141	100
	6	2224	740	702	420	179	141	70
	6	2764	920	882	600	179	141	100
	7	2434	810	772	490	179	141	70
	8	2644	880	842	560	179	141	70
	9	2854	950	912	630	179	141	70

U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	B2	C	D	G	P
36	2	2420	805,5	767	420	212	173,5	210
	2	2840	945,5	907	560	212	173,5	280
	3	2420	805,5	767	420	212	173,5	140
	3	3050	1015,5	977	630	212	173,5	210
	4	2360	785,5	747	400	212	173,5	100
	4	2840	945,5	907	560	212	173,5	140
	5	2210	735,5	697	350	212	173,5	70
	5	2660	885,5	847	500	212	173,5	100
	6	2420	805,5	767	420	212	173,5	70
	6	2960	985,5	947	600	212	173,5	100
	7	2630	875,5	837	490	212	173,5	70
	8	2840	945,5	907	560	212	173,5	70
	9	3050	1015,5	977	630	212	173,5	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12331097 000 00	Scale 1:10	
Chkd.	19.06.2026	MONDINN	Change no. 1143366		
Stand.	25.06.2026	CRESTANIN			


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 26 kV, 36 kV-
- for bridge connection-

SERIAL NUMBER –
MATERIAL NUMBER 101958110E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	B2	C	D	G	P
52	2	2338	778	740	280	268	230	140
	2	2758	918	880	420	268	230	210
	3	2398	798	760	300	268	230	100
	3	2758	918	880	420	268	230	140
	4	2338	778	740	280	268	230	70
	4	2698	898	860	400	268	230	100
	5	2548	848	810	350	268	230	70
	5	2998	998	960	500	268	230	100
	6	2758	918	880	420	268	230	70
	7	2968	988	950	490	268	230	70

U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	B2	C	D	G	P
73	2	2600	865,5	827	200	352	313,5	100
	2	2840	945,5	907	280	352	313,5	140
	3	2630	875,5	837	210	352	313,5	70
	3	2900	965,5	927	300	352	313,5	100
	4	2840	945,5	907	280	352	313,5	70
	5	3050	1015,5	977	350	352	313,5	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12960796 000 00	Scale 1:10	
Chkd.	19.06.2026	MONDINN	Change no. 1143366		
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED


DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 52 kV, 73 kV
– for bridge connection–


SERIAL NUMBER –


MATERIAL NUMBER 101958120E

SHEET 1 / 1

A3







U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	B2	C	D	G	M	P
26	2	1318	460	422	140	179	141	115	70
	2	1543	520	482	200	179	141	160	100
	2	1808	600	562	280	179	141	185	140
	3	1598	530	492	210	179	141	185	70
	3	1943	620	582	300	179	141	260	100
	4	1878	600	562	280	179	141	255	70
	5	2158	670	632	350	179	141	325	70

U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	B2	C	D	G	M	P
36	2	1481	525,5	487	140	212	173,5	115	70
	2	1706	585,5	547	200	212	173,5	160	100
	2	1971	665,5	627	280	212	173,5	185	140
	3	1761	595,5	557	210	212	173,5	185	70
	3	2106	685,5	647	300	212	173,5	260	100
	4	2041	665,5	627	280	212	173,5	255	70

U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	B2	C	D	G	M	P
52	2	1763	638	600	140	268	230	115	70
	2	1988	698	660	200	268	230	160	100
	3	2043	708	670	210	268	230	185	70

U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	B2	C	D	G	M	P
73	2	2181	805,5	767	140	352	313,5	115	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 127601184 000 00	Scale	1:10
Chkd.	19.06.2026	MONDINN	Change no.	1143366	
Stand.	25.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED


DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 26 kV, 36 kV, 52 kV, 73 kV
– for bridge connection–


SERIAL NUMBER –


MATERIAL NUMBER 101958140E

SHEET 1 / 1

A3







U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	B2	C	D	G	M	P
26	2	2420	740	702	420	179	141	255	210
	2	2910	880	842	560	179	141	325	280
	3	2490	740	702	420	179	141	325	140
	3	3260	950	912	630	179	141	465	210
	4	2465	720	682	400	179	141	360	100
	4	3050	880	842	560	179	141	465	140
	5	2865	820	782	500	179	141	460	100
	6	2560	740	702	420	179	141	395	70
	6	3265	920	882	600	179	141	560	100
	7	2840	810	772	490	179	141	465	70
	8	3120	880	842	560	179	141	535	70
	9	3400	950	912	630	179	141	605	70

U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	B2	C	D	G	M	P
36	2	2615,5	805,5	767	420	212	173,5	255	210
	2	3105,5	945,5	907	560	212	173,5	325	280
	3	2685,5	805,5	767	420	212	173,5	325	140
	3	3455,5	1015,5	977	630	212	173,5	465	210
	4	2660,5	785,5	747	400	212	173,5	360	100
	4	3245,5	945,5	907	560	212	173,5	465	140
	5	2475,5	735,5	697	350	212	173,5	325	70
	5	3060,5	885,5	847	500	212	173,5	460	100
	6	2755,5	805,5	767	420	212	173,5	395	70
	6	3460,5	985,5	947	600	212	173,5	560	100
	7	3035,5	875,5	837	490	212	173,5	465	70
	8	3315,5	945,5	907	560	212	173,5	535	70
	9	3595,5	1015,5	977	630	212	173,5	605	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 127642I8 000 00	Scale 1:10	
Chkd.	19.06.2026	MONDINN	Change no. 1143366		
Stand.	25.06.2026	CRESTANIN			


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 26 kV, 36 kV
– for bridge connection–

SERIAL NUMBER –
MATERIAL NUMBER 101958150E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	B2	C	D	G	M	P
52	2	2464	778	740	280	268	230	185	140
	2	2954	918	880	420	268	230	255	210
	3	2599	798	760	300	268	230	260	100
	3	3024	918	880	420	268	230	325	140
	4	2534	778	740	280	268	230	255	70
	4	2999	898	860	400	268	230	360	100
	5	2814	848	810	350	268	230	325	70
	5	3399	998	960	500	268	230	460	100
	6	3094	918	880	420	268	230	395	70
	7	3374	988	950	490	268	230	465	70

U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	B2	C	D	G	M	P
73	2	2700,5	865,5	827	200	352	313,5	160	100
	2	2965,5	945,5	907	280	352	313,5	185	140
	3	2755,5	875,5	837	210	352	313,5	185	70
	3	3100,5	965,5	927	300	352	313,5	260	100
	4	3035,5	945,5	907	280	352	313,5	255	70
	5	3315,5	1015,5	977	350	352	313,5	325	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12965176 000 00	Scale 1:10	
Chkd.	19.06.2026	MONDINN	Change no. 1143366		
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED


DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 52 kV, 73 kV
- for bridge connection-


SERIAL NUMBER –

MATERIAL NUMBER 101958160E

SHEET 1 / 1

A3







U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	C	D	G	M	P
26	2	596	460	140	179	141	115	70
	2	701	520	200	179	141	160	100
	2	806	600	280	179	141	185	140
	2	1016	740	420	179	141	255	210
	2	1226	880	560	179	141	325	280
	3	736	530	210	179	141	185	70
	3	901	620	300	179	141	260	100
	3	1086	740	420	179	141	325	140
	3	1436	950	630	179	141	465	210
	3	1786	1160	840	179	141	605	280
	4	876	600	280	179	141	255	70
	4	1101	720	400	179	141	360	100
	4	1366	880	560	179	141	465	140
	4	1856	1160	840	179	141	675	210
	5	1016	670	350	179	141	325	70
	5	1301	820	500	179	141	460	100
	5	1646	1020	700	179	141	605	140
	6	1156	740	420	179	141	395	70
	6	1501	920	600	179	141	560	100
	7	1296	810	490	179	141	465	70
	7	1701	1020	700	179	141	660	100
	8	1436	880	560	179	141	535	70
	9	1576	950	630	179	141	605	70
	10	1716	1020	700	179	141	675	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12784566 000 00	Scale	
Chkd.	19.06.2026	MONDINN	Change no.	1:10	
Stand.	25.06.2026	CRESTANIN	1143366		


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
single phase, Um 26 kV-
- for bridge connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958170E
SHEET 1 / 1
A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.







U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	C	D	G	M	P
36	2	661,5	525,5	140	212	173,5	115	70
	2	766,5	585,5	200	212	173,5	160	100
	2	871,5	665,5	280	212	173,5	185	140
	2	1081,5	805,5	420	212	173,5	255	210
	2	1291,5	945,5	560	212	173,5	325	280
	3	801,5	595,5	210	212	173,5	185	70
	3	966,5	685,5	300	212	173,5	260	100
	3	1151,5	805,5	420	212	173,5	325	140
	3	1501,5	1015,5	630	212	173,5	465	210
	3	1851,5	1225,5	840	212	173,5	605	280
	4	941,5	665,5	280	212	173,5	255	70
	4	1166,5	785,5	400	212	173,5	360	100
	4	1431,5	945,5	560	212	173,5	465	140
	4	1921,5	1225,5	840	212	173,5	675	210
	5	1081,5	735,5	350	212	173,5	325	70
	5	1366,5	885,5	500	212	173,5	460	100
	5	1711,5	1085,5	700	212	173,5	605	140
	6	1221,5	805,5	420	212	173,5	395	70
	6	1566,5	985,5	600	212	173,5	560	100
	6	1991,5	1225,5	840	212	173,5	745	140
	7	1361,5	875,5	490	212	173,5	465	70
	7	1766,5	1085,5	700	212	173,5	660	100
	8	1501,5	945,5	560	212	173,5	535	70
	8	1966,5	1185,5	800	212	173,5	760	100
	9	1641,5	1015,5	630	212	173,5	605	70
	10	1781,5	1085,5	700	212	173,5	675	70
	11	1921,5	1155,5	770	212	173,5	745	70


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 129749711 000 00	Scale	1:10
Chkd.	19.06.2026	MONDINN	Change no.	1143366	
Stand.	26.06.2026	CRESTANIN			


DIMENSION IN mm EXCEPT AS NOTED

MR

DE-ENERGIZED TAP-CHANGER CAPT® 040+
single phase, Um 36 kV-
- for bridge connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958180E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	C	D	G	M	P
52	2	774	638	140	268	230	115	70
	2	879	698	200	268	230	160	100
	2	984	778	280	268	230	185	140
	2	1194	918	420	268	230	255	210
	2	1404	1058	560	268	230	325	280
	3	914	708	210	268	230	185	70
	3	1079	798	300	268	230	260	100
	3	1264	918	420	268	230	325	140
	3	1614	1128	630	268	230	465	210
	3	1964	1338	840	268	230	605	280
	4	1054	778	280	268	230	255	70
	4	1279	898	400	268	230	360	100
	4	1544	1058	560	268	230	465	140
	4	2034	1338	840	268	230	675	210
	4	2524	1618	1120	268	230	885	280
	5	1194	848	350	268	230	325	70
	5	1479	998	500	268	230	460	100
	5	1824	1198	700	268	230	605	140
	5	2454	1548	1050	268	230	885	210
	6	1334	918	420	268	230	395	70
	6	1679	1098	600	268	230	560	100
	6	2104	1338	840	268	230	745	140
	7	1474	988	490	268	230	465	70
	7	1879	1198	700	268	230	660	100
	7	2384	1478	980	268	230	885	140
	8	1614	1058	560	268	230	535	70
	8	2079	1298	800	268	230	760	100
	9	1754	1128	630	268	230	605	70
	9	2279	1398	900	268	230	860	100
	10	1894	1198	700	268	230	675	70
	10	2479	1498	1000	268	230	960	100
	11	2034	1268	770	268	230	745	70
	12	2174	1338	840	268	230	815	70
	13	2314	1408	910	268	230	885	70
	14	2454	1478	980	268	230	955	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	25.08.2026	CRESTANIN	SED 129749780000 1	Scale	1:10
Chkd.	25.08.2026	MONDINN	Change no.	1147509	
Stand.	25.08.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED

De-Energized Tap-Changer CAPT® 040+
single phase, Um 52 kV-
- for bridge connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958190E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	C	D	G	M	P
73	2	941,5	805,5	140	352	313,5	115	70
	2	1046,5	865,5	200	352	313,5	160	100
	2	1151,5	945,5	280	352	313,5	185	140
	3	1081,5	875,5	210	352	313,5	185	70
	3	1246,5	965,5	300	352	313,5	260	100
	3	1431,5	1085,5	420	352	313,5	325	140
	4	1221,5	945,5	280	352	313,5	255	70
	4	1446,5	1065,5	400	352	313,5	360	100
	4	1711,5	1225,5	560	352	313,5	465	140
	5	1361,5	1015,5	350	352	313,5	325	70
	5	1646,5	1165,5	500	352	313,5	460	100
	5	1991,5	1365,5	700	352	313,5	605	140
	6	1501,5	1085,5	420	352	313,5	395	70
	6	1846,5	1265,5	600	352	313,5	560	100
	6	2271,5	1505,5	840	352	313,5	745	140
	7	1641,5	1155,5	490	352	313,5	465	70
	7	2046,5	1365,5	700	352	313,5	660	100
	7	2551,5	1645,5	980	352	313,5	885	140
	8	1781,5	1225,5	560	352	313,5	535	70
	8	2246,5	1465,5	800	352	313,5	760	100
	8	2831,5	1785,5	1120	352	313,5	1025	140
	9	1921,5	1295,5	630	352	313,5	605	70
	9	2446,5	1565,5	900	352	313,5	860	100
	9	3111,5	1925,5	1260	352	313,5	1165	140
	10	2061,5	1365,5	700	352	313,5	675	70
	10	2646,5	1665,5	1000	352	313,5	960	100
	10	3391,5	2065,5	1400	352	313,5	1305	140
	11	2201,5	1435,5	770	352	313,5	745	70
	11	2846,5	1765,5	1100	352	313,5	1060	100
	12	2341,5	1505,5	840	352	313,5	815	70
	12	3046,5	1865,5	1200	352	313,5	1160	100
	13	2481,5	1575,5	910	352	313,5	885	70
	13	3246,5	1965,5	1300	352	313,5	1260	100
	14	2621,5	1645,5	980	352	313,5	955	70
	15	2761,5	1715,5	1050	352	313,5	1025	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 129749820000	Scale	
Chkd.	19.06.2026	MONDINN	Change no.	1:10	
Stand.	26.06.2026	CRESTANIN	1143366		


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
single phase, Um 73 kV-
- for bridge connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958200E
SHEET 1/1
A3







U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	C	D	G	M	P
73	2	1361,5	1085,5	420	352	313,5	255	210
	2	1571,5	1225,5	560	352	313,5	325	280
	3	1781,5	1295,5	630	352	313,5	465	210
	3	2131,5	1505,5	840	352	313,5	605	280
	4	2201,5	1505,5	840	352	313,5	675	210
	4	2691,5	1785,5	1120	352	313,5	885	280
	5	2621,5	1715,5	1050	352	313,5	885	210
	5	3251,5	2065,5	1400	352	313,5	1165	280
	6	3041,5	1925,5	1260	352	313,5	1095	210
	7	3461,5	2135,5	1470	352	313,5	1305	210

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		
Dftr.	16.06.2026	CRESTANIN	SED 13163292 000 00	Scale	1:10
Chkd.	19.06.2026	MONDINN	Change no.		
Stand.	25.06.2026	CRESTANIN	1143366		


Projection method


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
single phase, Um 73 kV-
- for bridge connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958210E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)								
		A	B1	B2	C	D	G	K1	K2	P
26	2	1174	390	352	70	179	141	249	352	70
	2	1264	420	382	100	179	141	279	382	100
	2	1384	460	422	140	179	141	319	422	140
	3	1384	460	422	140	179	141	319	422	70
	3	1564	520	482	200	179	141	379	482	100
	3	1804	600	562	280	179	141	459	562	140
	4	1594	530	492	210	179	141	389	492	70
	4	1864	620	582	300	179	141	479	582	100
	5	1804	600	562	280	179	141	459	562	70

U_m (kV)	N° Positions	Dimensions (mm)								
		A	B1	B2	C	D	G	K1	K2	P
36	2	1370	455,5	417	70	212	173,5	282	417	70
	2	1460	485,5	447	100	212	173,5	312	447	100
	2	1580	525,5	487	140	212	173,5	352	487	140
	3	1580	525,5	487	140	212	173,5	352	487	70
	3	1760	585,5	547	200	212	173,5	412	547	100
	3	2000	665,5	627	280	212	173,5	492	627	140
	4	1790	595,5	557	210	212	173,5	422	557	70
	4	2060	685,5	647	300	212	173,5	512	647	100
	5	2000	665,5	627	280	212	173,5	492	627	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12342929 000 00	Scale	1:10
Chkd.	22.06.2026	MONDINN	Change no.	1143366	
Stand.	25.06.2026	CRESTANIN			


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 26 kV, 36 kV-
- for linear connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958220E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)								
		A	B1	B2	C	D	G	K1	K2	P
52	2	1708	568	530	70	268	230	338	530	70
	2	1798	598	560	100	268	230	368	560	100
	2	1918	638	600	140	268	230	408	600	140
	3	1918	638	600	140	268	230	408	600	70
	3	2098	698	660	200	268	230	468	660	100
	3	2338	778	740	280	268	230	548	740	140
	4	2128	708	670	210	268	230	478	670	70
	4	2398	798	760	300	268	230	568	760	100
	5	2338	778	740	280	268	230	548	740	70

U_m (kV)	N° Positions	Dimensions (mm)								
		A	B1	B2	C	D	G	K1	K2	P
73	2	2210	735,5	697	70	352	313,5	422	697	70
	2	2300	765,5	727	100	352	313,5	452	727	100
	2	2420	805,5	767	140	352	313,5	492	767	140
	3	2420	805,5	767	140	352	313,5	492	767	70
	3	2600	865,5	827	200	352	313,5	552	827	100
	3	2840	945,5	907	280	352	313,5	632	907	140
	4	2630	875,5	837	210	352	313,5	562	837	70
	4	2900	965,5	927	300	352	313,5	652	927	100
	5	2840	945,5	907	280	352	313,5	632	907	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12975811 000 00	Scale	1:10
Chkd.	22.06.2026	MONDINN	Change no.	1143366	
Stand.	26.06.2026	CRESTANIN			


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 52 kV, 73 kV-
- for linear connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958290E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)								
		A	B1	B2	C	D	G	K1	K2	P
26	4	2224	740	702	420	179	141	389	702	140
	5	2164	720	682	400	179	141	379	682	100
	5	2644	880	842	560	179	141	459	842	140
	6	2014	670	632	350	179	141	354	632	70
	6	2464	820	782	500	179	141	429	782	100
	7	2224	740	702	420	179	141	389	702	70
	7	2764	920	882	600	179	141	479	882	100
	8	2434	810	772	490	179	141	424	772	70
	9	2644	880	842	560	179	141	459	842	70
	10	2854	950	912	630	179	141	494	912	70

U_m (kV)	N° Positions	Dimensions (mm)								
		A	B1	B2	C	D	G	K1	K2	P
36	4	2420	805,5	767	420	212	173,5	422	767	140
	5	2360	785,5	747	400	212	173,5	412	747	100
	5	2840	945,5	907	560	212	173,5	492	907	140
	6	2210	735,5	697	350	212	173,5	387	697	70
	6	2660	885,5	847	500	212	173,5	462	847	100
	7	2420	805,5	767	420	212	173,5	422	767	70
	7	2960	985,5	947	600	212	173,5	512	947	100
	8	2630	875,5	837	490	212	173,5	457	837	70
	9	2840	945,5	907	560	212	173,5	492	907	70
	10	3050	1015,5	977	630	212	173,5	527	977	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12348605 000 00	Scale	1:10
Chkd.	22.06.2026	MONDINN	Change no.	1143366	
Stand.	25.06.2026	CRESTANIN			


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 26 kV, 36 kV-
- for linear connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958300E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)								
		A	B1	B2	C	D	G	K1	K2	P
52	4	2758	918	880	420	268	230	478	880	140
	5	2698	898	860	400	268	230	468	860	100
	6	2548	848	810	350	268	230	443	810	70
	6	2998	998	960	500	268	230	518	960	100
	7	2758	918	880	420	268	230	478	880	70
	8	2968	988	950	490	268	230	513	950	70

U_m (kV)	N° Positions	Dimensions (mm)								
		A	B1	B2	C	D	G	K1	K2	P
73	6	3050	1015,5	977	350	352	313,5	527	977	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12979973 000 00	Scale	1:10
Chkd.	22.06.2026	MONDINN	Change no.	1143366	
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED


DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 52 kV, 73 kV-
- for linear connection-


SERIAL NUMBER –


MATERIAL NUMBER 101958330E

SHEET 1 / 1

A3







U_m (kV)	N° Positions	Dimensions (mm)									
		A	B1	B2	C	D	G	M	K1	K2	P
26	2	1230	390	352	70	179	141	115	249	352	70
	2	1365	420	382	100	179	141	160	279	382	100
	2	1510	460	422	140	179	141	185	319	422	140
	3	1510	460	422	140	179	141	185	319	422	70
	3	1765	520	482	200	179	141	260	379	482	100
	3	2070	600	562	280	179	141	325	459	562	140
	4	1790	530	492	210	179	141	255	389	492	70
	4	2165	620	582	300	179	141	360	479	582	100
	5	2070	600	562	280	179	141	325	459	562	70

U_m (kV)	N° Positions	Dimensions (mm)									
		A	B1	B2	C	D	G	M	K1	K2	P
36	2	1425,5	455,5	417	70	212	173,5	115	282	417	70
	2	1560,5	485,5	447	100	212	173,5	160	312	447	100
	2	1705,5	525,5	487	140	212	173,5	185	352	487	140
	3	1705,5	525,5	487	140	212	173,5	185	352	487	70
	3	1960,5	585,5	547	200	212	173,5	260	412	547	100
	3	2265,5	665,5	627	280	212	173,5	325	492	627	140
	4	1985,5	595,5	557	210	212	173,5	255	422	557	70
	4	2360,5	685,5	647	300	212	173,5	360	512	647	100
	5	2265,5	665,5	627	280	212	173,5	325	492	627	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 1277714476 000 00	Scale	1:10
Chkd.	22.06.2026	MONDINN	Change no.	1143366	
Stand.	25.06.2026	CRESTANIN			


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 26 kV, 36 kV-
- for linear connection-

SERIAL NUMBER –
MATERIAL NUMBER 101958340E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)									
		A	B1	B2	C	D	G	M	K1	K2	P
52	2	1764	568	530	70	268	230	115	338	530	70
	2	1899	598	560	100	268	230	160	368	560	100
	2	2044	638	600	140	268	230	185	408	600	140
	3	2044	638	600	140	268	230	185	408	600	70
	3	2299	698	660	200	268	230	260	468	660	100
	3	2604	778	740	280	268	230	325	548	740	140
	4	2324	708	670	210	268	230	255	478	670	70
	4	2699	798	760	300	268	230	360	568	760	100
	5	2604	778	740	280	268	230	325	548	740	70

U_m (kV)	N° Positions	Dimensions (mm)									
		A	B1	B2	C	D	G	M	K1	K2	P
73	2	2265,5	735,5	697	70	352	313,5	115	422	697	70
	2	2400,5	765,5	727	100	352	313,5	160	452	727	100
	2	2545,5	805,5	767	140	352	313,5	185	492	767	140
	3	2545,5	805,5	767	140	352	313,5	185	492	767	70
	3	2800,5	865,5	827	200	352	313,5	260	552	827	100
	3	3105,5	945,5	907	280	352	313,5	325	632	907	140
	4	2825,5	875,5	837	210	352	313,5	255	562	837	70
	4	3200,5	965,5	927	300	352	313,5	360	652	927	100
	5	3105,5	945,5	907	280	352	313,5	325	632	907	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12980878 000 00	Scale	1:10
Chkd.	22.06.2026	MONDINN	Change no.	1143366	
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED

MR


DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 52 kV, 73 kV-
- for linear connection-


SERIAL NUMBER –


MATERIAL NUMBER 101958350E

SHEET 1 / 1

A3







U_m (kV)	N° Positions	Dimensions (mm)									
		A	B1	B2	C	D	G	M	K1	K2	P
26	4	2630	740	702	420	179	141	465	389	702	140
	5	2565	720	682	400	179	141	460	379	682	100
	5	3190	880	842	560	179	141	605	459	842	140
	6	2350	670	632	350	179	141	395	354	632	70
	6	2965	820	782	500	179	141	560	429	782	100
	7	2630	740	702	420	179	141	465	389	702	70
	7	3365	920	882	600	179	141	660	479	882	100
	8	2910	810	772	490	179	141	535	424	772	70
	9	3190	880	842	560	179	141	605	459	842	70
	10	3470	950	912	630	179	141	675	494	912	70

U_m (kV)	N° Positions	Dimensions (mm)									
		A	B1	B2	C	D	G	M	K1	K2	P
36	4	2825,5	805,5	767	420	212	173,5	465	422	767	140
	5	2760,5	785,5	747	400	212	173,5	460	412	747	100
	5	3385,5	945,5	907	560	212	173,5	605	492	907	140
	6	2545,5	735,5	697	350	212	173,5	395	387	697	70
	6	3160,5	885,5	847	500	212	173,5	560	462	847	100
	7	2825,5	805,5	767	420	212	173,5	465	422	767	70
	7	3560,5	985,5	947	600	212	173,5	660	512	947	100
	8	3105,5	875,5	837	490	212	173,5	535	457	837	70
	9	3385,5	945,5	907	560	212	173,5	605	492	907	70
	10	3665,5	1015,5	977	630	212	173,5	675	527	977	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	22.06.2026	CRESTANIN	SED 127758d3 000 00	Scale 1:10	
Chkd.	22.06.2026	MONDINN	Change no. 1143366		
Stand.	25.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED

MR


DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 26 kV, 36 kV-
- for linear connection-


SERIAL NUMBER –


MATERIAL NUMBER 101958360E

SHEET 1 / 1

A3







U_m (kV)	N° Positions	Dimensions (mm)									
		A	B1	B2	C	D	G	M	K1	K2	P
52	4	3164	918	880	420	268	230	465	478	880	140
	5	3099	898	860	400	268	230	460	468	860	100
	6	2884	848	810	350	268	230	395	443	810	70
	6	3499	998	960	500	268	230	560	518	960	100
	7	3164	918	880	420	268	230	465	478	880	70
	8	3444	988	950	490	268	230	535	513	950	70

U_m (kV)	N° Positions	Dimensions (mm)									
		A	B1	B2	C	D	G	M	K1	K2	P
73	6	3385,5	1015,5	977	350	352	313,5	395	527	977	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12981504 000 00	Scale 1:10	
Chkd.	22.06.2026	MONDINN	Change no. 1143366		
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED


DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 52 kV, 73 kV-
- for linear connection-


SERIAL NUMBER –


MATERIAL NUMBER 101958370E

SHEET 1 / 1

A3







Voltage (kV)	N° Positions	Dimensions (mm)							
		A	B1	C	D	G	M	K1	P
26	2	526	390	70	179	141	115	249	70
	2	601	420	100	179	141	160	279	100
	2	666	460	140	179	141	185	319	140
	3	666	460	140	179	141	185	319	70
	3	801	520	200	179	141	260	379	100
	3	946	600	280	179	141	325	459	140
	4	806	530	210	179	141	255	389	70
	4	1001	620	300	179	141	360	479	100
	5	946	600	280	179	141	325	459	70

Voltage (kV)	N° Positions	Dimensions (mm)							
		A	B1	C	D	G	M	K1	P
36	2	591,5	455,5	70	212	173,5	115	282	70
	2	666,5	485,5	100	212	173,5	160	312	100
	2	731,5	525,5	140	212	173,5	185	352	140
	3	731,5	525,5	140	212	173,5	185	352	70
	3	866,5	585,5	200	212	173,5	260	412	100
	3	1011,5	665,5	280	212	173,5	325	492	140
	4	871,5	595,5	210	212	173,5	255	422	70
	4	1066,5	685,5	300	212	173,5	360	512	100
	5	1011,5	665,5	280	212	173,5	325	492	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12830354 000 00	Scale 1:10	
Chkd.	22.06.2026	MONDINN	Change no. 1143366		
Stand.	25.06.2026	CRESTANIN			


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
single phase, Um 26 kV, 36 kV-
- for linear connection-

SERIAL NUMBER –
MATERIAL NUMBER 101958380E
SHEET 1 / 1
A3







Voltage (kV)	N° Positions	Dimensions (mm)							
		A	B1	C	D	G	M	K1	P
52	2	704	568	70	268	230	115	338	70
	2	779	598	100	268	230	160	368	100
	2	844	638	140	268	230	185	408	140
	3	844	638	140	268	230	185	408	70
	3	979	698	200	268	230	260	468	100
	3	1124	778	280	268	230	325	548	140
	4	984	708	210	268	230	255	478	70
	4	1179	798	300	268	230	360	568	100
	5	1124	778	280	268	230	325	548	70

Voltage (kV)	N° Positions	Dimensions (mm)							
		A	B1	C	D	G	M	K1	P
73	2	871,5	735,5	70	352	313,5	115	422	70
	2	946,5	765,5	100	352	313,5	160	452	100
	2	1011,5	805,5	140	352	313,5	185	492	140
	3	1011,5	805,5	140	352	313,5	185	492	70
	3	1146,5	865,5	200	352	313,5	260	552	100
	3	1291,5	945,5	280	352	313,5	325	632	140
	4	1151,5	875,5	210	352	313,5	255	562	70
	4	1346,5	965,5	300	352	313,5	360	652	100
	5	1291,5	945,5	280	352	313,5	325	632	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12981617 000 00	Scale 1:10	
Chkd.	22.06.2026	MONDINN	Change no. 1143366		
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED


DE-ENERGIZED TAP-CHANGER CAPT® 040+
single phase, Um 52 kV, 73 kV
- for linear connection-


SERIAL NUMBER –


MATERIAL NUMBER 101958390E

SHEET 1 / 1

A3







U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	C	D	G	M	K1	P
26	4	1226	740	420	179	141	465	389	140
	5	1201	720	400	179	141	460	379	100
	5	1506	880	560	179	141	605	459	140
	6	1086	670	350	179	141	395	354	70
	6	1401	820	500	179	141	560	429	100
	7	1226	740	420	179	141	465	389	70
	7	1601	920	600	179	141	660	479	100
	8	1366	810	490	179	141	535	424	70
	9	1506	880	560	179	141	605	459	70
	10	1646	950	630	179	141	675	494	70

U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	C	D	G	M	K1	P
36	4	1291,5	805,5	420	212	173,5	465	422	140
	5	1266,5	785,5	400	212	173,5	460	412	100
	5	1571,5	945,5	560	212	173,5	605	492	140
	6	1151,5	735,5	350	212	173,5	395	387	70
	6	1466,5	885,5	500	212	173,5	560	462	100
	6	1851,5	1085,5	700	212	173,5	745	562	140
	7	1291,5	805,5	420	212	173,5	465	422	70
	7	1666,5	985,5	600	212	173,5	660	512	100
	8	1431,5	875,5	490	212	173,5	535	457	70
	8	1866,5	1085,5	700	212	173,5	760	562	100
	9	1571,5	945,5	560	212	173,5	605	492	70
	10	1711,5	1015,5	630	212	173,5	675	527	70
	11	1851,5	1085,5	700	212	173,5	745	562	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 128620772 000 00	Scale 1:10	
Chkd.	22.06.2026	MONDINN	Change no. 1143366		
Stand.	25.06.2026	CRESTANIN			


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
single phase, Um 26 kV, 36 kV-
- for linear connection-

SERIAL NUMBER –
MATERIAL NUMBER 101958400E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	C	D	G	M	K1	P
52	4	1404	918	420	268	230	465	478	140
	5	1379	898	400	268	230	460	468	100
	5	1684	1058	560	268	230	605	548	140
	6	1264	848	350	268	230	395	443	70
	6	1579	998	500	268	230	560	518	100
	6	1964	1198	700	268	230	745	618	140
	7	1404	918	420	268	230	465	478	70
	7	1779	1098	600	268	230	660	568	100
	7	2244	1338	840	268	230	885	688	140
	8	1544	988	490	268	230	535	513	70
	8	1979	1198	700	268	230	760	618	100
	9	1684	1058	560	268	230	605	548	70
	9	2179	1298	800	268	230	860	668	100
	10	1824	1128	630	268	230	675	583	70
	10	2379	1398	900	268	230	960	718	100
	11	1964	1198	700	268	230	745	618	70
	12	2104	1268	770	268	230	815	653	70
	13	2244	1338	840	268	230	885	688	70
	14	2384	1408	910	268	230	955	723	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12982229 000 00	Scale	1:10
Chkd.	22.06.2026	MONDINN	Change no.	1143366	
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED


DE-ENERGIZED TAP-CHANGER CAPT® 040+
single phase, Um 52 kV-
- for linear connection-


SERIAL NUMBER –


MATERIAL NUMBER 101958410E

SHEET 1 / 1

A3







U_m (kV)	N° Positions	Dimensions (mm)							
		A	B1	C	D	G	M	K1	P
73	4	1571,5	1085,5	420	352	313,5	465	562	140
	5	1546,5	1065,5	400	352	313,5	460	552	100
	5	1851,5	1225,5	560	352	313,5	605	632	140
	6	1431,5	1015,5	350	352	313,5	395	527	70
	6	1746,5	1165,5	500	352	313,5	560	602	100
	6	2131,5	1365,5	700	352	313,5	745	702	140
	7	1571,5	1085,5	420	352	313,5	465	562	70
	7	1946,5	1265,5	600	352	313,5	660	652	100
	7	2411,5	1505,5	840	352	313,5	885	772	140
	8	1711,5	1155,5	490	352	313,5	535	597	70
	8	2146,5	1365,5	700	352	313,5	760	702	100
	8	2691,5	1645,5	980	352	313,5	1025	842	140
	9	1851,5	1225,5	560	352	313,5	605	632	70
	9	2346,5	1465,5	800	352	313,5	860	752	100
	9	2971,5	1785,5	1120	352	313,5	1165	912	140
	10	1991,5	1295,5	630	352	313,5	675	667	70
	10	2546,5	1565,5	900	352	313,5	960	802	100
	10	3251,5	1925,5	1260	352	313,5	1305	982	140
	11	2131,5	1365,5	700	352	313,5	745	702	70
	11	2746,5	1665,5	1000	352	313,5	1060	852	100
	12	2271,5	1435,5	770	352	313,5	815	737	70
	12	2946,5	1765,5	1100	352	313,5	1160	902	100
	13	2411,5	1505,5	840	352	313,5	885	772	70
	13	3146,5	1865,5	1200	352	313,5	1260	952	100
	14	2551,5	1575,5	910	352	313,5	955	807	70
	15	2691,5	1645,5	980	352	313,5	1025	842	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12982235 000 00		
Chkd.	22.06.2026	MONDINN	Change no.	Scale	
Stand.	26.06.2026	CRESTANIN	1143366	1:10	


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
single phase, Um 73 kV-
- for linear connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958420E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)					
		A	B1	C	D	G	P
26	2	1560	600	280	179	141	70

U_m (kV)	N° Positions	Dimensions (mm)					
		A	B1	C	D	G	P
36	2	1691	665,5	280	212	173,5	70


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12351967 000 00		
Chkd.	22.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	1:10	


DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 26 kV, 36 kV-
- for series parallel connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958430E
SHEET 1 / 1
A3







U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	B2	C	D	G	P
26	2	2164	720	682	400	179	141	100
	2	2644	880	842	560	179	141	140

U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	B2	C	D	G	P
36	2	2360	785,5	747	400	212	173,5	100
	2	2840	945,5	907	560	212	173,5	140

U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	B2	C	D	G	P
52	2	2338	778	740	280	268	230	70
	2	2698	898	860	400	268	230	100

U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	B2	C	D	G	P
73	2	2840	945,5	907	280	352	313,5	70

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12882359 000 00	Scale	1:10
Chkd.	22.06.2026	MONDINN	Change no.	1143366	
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED


DE-ENERGIZED TAP-CHANGER CAPT® 040+
Um 26 kV, 36 kV, 52 kV, 73 kV
- for series parallel connection-


SERIAL NUMBER –


MATERIAL NUMBER 101958440E

SHEET 1/ 1

A3







U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	C	D	G	M	P
26	2	736	600	280	179	141	115	70
	2	901	720	400	179	141	160	100
	2	1086	880	560	179	141	185	140
	2	1436	1160	840	179	141	255	210
	2	1786	1440	1120	179	141	325	280

U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	C	D	G	M	P
36	2	801,5	665,5	280	212	173,5	115	70
	2	966,5	785,5	400	212	173,5	160	100
	2	1151,5	945,5	560	212	173,5	185	140
	2	1501,5	1225,5	840	212	173,5	255	210
	2	1851,5	1505,5	1120	212	173,5	325	280

U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	C	D	G	M	P
52	2	914	778	280	268	230	115	70
	2	1079	898	400	268	230	160	100
	2	1264	1058	560	268	230	185	140
	2	1614	1338	840	268	230	255	210
	2	1964	1618	1120	268	230	325	280

U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	C	D	G	M	P
73	2	1081,5	945,5	280	352	313,5	115	70
	2	1246,5	1065,5	400	352	313,5	160	100
	2	1431,5	1225,5	560	352	313,5	185	140

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	25.08.2026	CRESTANIN	SED 12899565 000 01	Scale 1:10	
Chkd.	25.08.2026	MONDINN	Change no. 1147509		
Stand.	25.08.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED


De-Energized Tap-Changer CAPT® 040+
Um 26 kV, 36 kV, 52 kV, 73 kV
- for series parallel connection-


SERIAL NUMBER –


MATERIAL NUMBER 101958450E

SHEET 1 / 1

A3







U_m (kV)	N° Positions	Dimensions (mm)						
		A	B1	C	D	G	M	P
73	2	1781,5	1505,5	840	352	313,5	255	210
	2	2131,5	1785,5	1120	352	313,5	325	280

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		
Dftr.	25.08.2026	CRESTANIN	SED 13159652 000 02		
Chkd.	25.08.2026	MONDINN	Change no.	Scale	1:10
Stand.	25.08.2026	CRESTANIN	1147509		


Projection method

DIMENSION IN mm EXCEPT AS NOTED


De-Energized Tap-Changer CAPT® 040+
Um 73 kV
- for series parallel connection-

SERIAL NUMBER
-
MATERIAL NUMBER 101958460E
SHEET 1/ 1
A3


GEAR SUPPORT POSITIONS



NUMBER OF STAGES PER DECK



NUMBER OF COLUMNS



Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13163982 000 00		
Chkd.	25.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	1:15	

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Gear support position, Number of stages and columns


SERIAL NUMBER –

MATERIAL NUMBER 101958520E

SHEET 1 / 1


A3

DECKS



Distances between decks	
Um (kV)	Distance (mm)
26	120
36	175
52	200
73	For this Um, decks are not available

COLUMNS



Distances between columns	
Um (kV)	Distance (mm)
26	Minimun 300
36	Minimun 300
52	Minimun 300
73	Without equipotential rings 300
73	With equipotential rings 400

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13155718 000 00		
Chkd.	25.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	1:10	

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Decks and columns


SERIAL NUMBER –

MATERIAL NUMBER 101958530E


SHEET 1 / 1

A3


DIRECT SHAFT OUTPUT "A"




BEVEL GEAR AT 0° "B"




BEVEL GEAR AT 90° "C"



BEVEL GEAR AT 180° "D"



BEVEL GEAR AT 270° "E"



Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13400980 000 00		
Chkd.	25.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	1:10	

DIMENSION IN mm EXCEPT AS NOTED

MR

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Shaft output


SERIAL NUMBER
–


MATERIAL NUMBER
101973670E


SHEET
1 / 1


A3


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.














	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 12870346 000 00		
Chkd.	22.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	1:5	

DIMENSION IN mm EXCEPT AS NOTED

MR

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Bevel gear support


SERIAL NUMBER
–


MATERIAL NUMBER
101958540E


SHEET
1 / 1


A3


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.











	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 128710772 000 00		
Chkd.	22.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	1:5	

DIMENSION IN mm EXCEPT AS NOTED

MR

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Intermediate support


SERIAL NUMBER
–


MATERIAL NUMBER
101958560E


SHEET
1 / 1


A3

FLAT FIXED CONTACTS
MAXIMUM CURRENT 1000 A













FLAT FIXED CONTACTS
MAXIMUM CURRENT 1600 A









Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		
Dftr.	16.06.2026	CRESTANIN	SED 12874995 000 00		
Chkd.	22.06.2026	MONDINN	Change no.	Scale	1:2
Stand.	25.06.2026	CRESTANIN	1143366		

Projection method

DIMENSION IN mm EXCEPT AS NOTED

MR

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Flat fixed contacts

SERIAL NUMBER
–

MATERIAL NUMBER
101958570E


SHEET
1 / 1


A3


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.

THREADED FIXED CONTACTS

MAXIMUM CURRENT 1000 A










1 – THREADED CONTACT
2 – CABLE LUG (NOT PROVIDED)
3 – FLAT WASHER M20
4 – HEXAGONAL NUT M20 ISO 4032
5 – HEXAGONAL NUT M20 ISO 4035

THREADED FIXED CONTACTS

MAXIMUM CURRENT 1600 A







1 – THREADED CONTACT
2 – CABLE LUG (NOT PROVIDED)
3 – FLAT WASHER M24
4 – HEXAGONAL NUT M24 ISO 4032
5 – HEXAGONAL NUT M24 ISO 4035

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 12876519 000 00	Scale	
Chkd.	25.06.2026	MONDINN	Change no.	1:2	
Stand.	25.06.2026	CRESTANIN	1143366		

DIMENSION IN mm EXCEPT AS NOTED

MR

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Threaded fixed contacts


SERIAL NUMBER
–


MATERIAL NUMBER
101958580E


SHEET
1 / 1


A3

EQUIPOTENTIAL RINGS













EQUIPOTENTIAL RINGS WITH PRESSBOARD SHIELD









Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 13122407 000 00		
Chkd.	19.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	1:5	

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Equipotential ring, pressboard shield

SERIAL NUMBER
–


MATERIAL NUMBER
101958590E

SHEET
1 / 1


A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


LAYOUT1A




LAYOUT1AI



LAYOUT1B



LAYOUT1BI



(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DIRECT DRIVE ON COVER
OPTIONS:
070-1.12.212
070-1.12.212BE

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 12991620 000 00	Scale	1:20
Chkd.	25.06.2026	MONDINN	Change no.		
Stand.	26.06.2026	CRESTANIN	1143366		

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer cover

SERIAL NUMBER
–


MATERIAL NUMBER
101958610E

SHEET
1 / 1


A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.

LAYOUT1C



LAYOUT1CI



(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DIRECT DRIVE ON COVER
OPTIONS:
070-1.12.212
070-1.12.212BE

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13143668 000 00		
Chkd.	25.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	1:20	

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer cover

SERIAL NUMBER
–


MATERIAL NUMBER
101958620E


SHEET
1 / 1

A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

LAYOUT2A









View A


LAYOUT2AI






View A 

LAYOUT2B









View A

LAYOUT2BI





View A 

(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DIRECT DRIVE ON WALL
OPTIONS:
070-1.12.212
070-1.12.212BE

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) CONICAL PLUG-IN COUPLING
OPTION:
070-1.12.211

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13046658 000 00	Scale 1:20	
Chkd.	25.06.2026	MONDINN	Change no. 1143366		
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED

MR

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER –


MATERIAL NUMBER 101958630E

SHEET 1 / 1

A3


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.

LAYOUT2C



View A

LAYOUT2CI



View A 

(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DIRECT DRIVE ON WALL
OPTIONS:
070-1.12.212
070-1.12.212BE

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) CONICAL PLUG-IN COUPLING
OPTION:
070-1.12.211

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name
Dftr.	25.06.2026	CRESTANIN
Chkd.	25.06.2026	MONDINN
Stand.	26.06.2026	CRESTANIN

Document no.		Projection method
SED 13113290 000 00		
Change no.	Scale	
1143366	1:20	

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–


MATERIAL NUMBER
101958640E

SHEET
1 / 1

A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.


LAYOUT2D





View A

LAYOUT2DI



View A 

(X) TRANSFORMER TANK BOTTOM
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DIRECT DRIVE ON WALL
OPTIONS:
070-1.12.208
070-1.12.209

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) CONICAL PLUG-IN COUPLING
OPTION:
070-1.12.211

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13116792 000 00	Scale 1:20	
Chkd.	25.06.2026	MONDINN	Change no. 1143366		
Stand.	26.06.2026	CRESTANIN			


DIMENSION IN mm EXCEPT AS NOTED


DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–
MATERIAL NUMBER 101958650E
SHEET 1 / 1
A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.


LAYOUT2E






View A 

LAYOUT2EI






 View A

	Name	Date
Dftr.	CRESTANIN	25.06.2026
Chkd.	MONDINN	25.06.2026
Stand.	CRESTANIN	25.06.2026

Document no.	Scale
SED 13147392 000 00	1:20
Change no.	
1143366	

Projection method 

(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DIRECT DRIVE ON WALL
OPTIONS:
070-1.12.212
070-1.12.212BE

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) CONICAL PLUG-IN COUPLING
OPTION:
070-1.12.211

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

DIMENSION IN mm EXCEPT AS NOTED

MR

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–


MATERIAL NUMBER
101958660E

SHEET
1 / 1

A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


LAYOUT3A






View A

LAYOUT3AI



View A 


LAYOUT3B





View A

LAYOUT3BI



View A 

(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DIRECT DRIVE ON COVER
OPTIONS:
070-1.12.212
070-1.12.212BE

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) CONICAL PLUG-IN COUPLING
OPTION:
070-1.12.211

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13047597 000 00	Scale 1:20	
Chkd.	25.06.2026	MONDINN	Change no. 1143366		
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED

MR

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–


MATERIAL NUMBER 101958670E

SHEET 1 / 1


A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

LAYOUT3C



View A



LAYOUT3CI

View A



(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DIRECT DRIVE ON WALL
OPTIONS:
070-1.12.212
070-1.12.212BE

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) CONICAL PLUG-IN COUPLING
OPTION:
070-1.12.211

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13117682 000 00	Scale 1:20	
Chkd.	25.06.2026	MONDINN	Change no. 1143366		
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–


MATERIAL NUMBER 101958680E

SHEET 1 / 1

A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.


LAYOUT3D





View A

LAYOUT3DI



View A 

(W) TRANSFORMER TANK BOTTOM
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DIRECT DRIVE ON WALL
OPTIONS:
070-1.12.208
070-1.12.209

(2) CONICAL PLUG-IN COUPLING
OPTIONS:
070-1.12.211

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13118608 000 00		
Chkd.	25.06.2026	MONDINN	Change no.	Scale	
Stand.	26.06.2026	CRESTANIN	1143366	1:20	

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–


MATERIAL NUMBER
101958690E

SHEET
1 / 1

A3


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.

LAYOUT3E



View A 

LAYOUT3EI



 View A

	Name	Date
Drawn	CRESTANIN	25.06.2026
Chkd.	MONDINN	25.06.2026
Stand.	CRESTANIN	25.06.2026

Document no.: SED 1314835 4 000 00
Change no.: 1143366
Scale: 1:20
Projection method

(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DIRECT DRIVE ON WALL
OPTIONS:
070-1.12.212
070-1.12.212BE

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) CONICAL PLUG-IN COUPLING
OPTION:
070-1.12.211

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–


MATERIAL NUMBER
101958700E

SHEET
1 / 1

A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.


LAYOUT4A



A

View A

LAYOUT4AI



A

View A

	Name	Date
Dftr.	CRESTANIN	25.06.2026
Chkd.	MONDINN	25.06.2026
Stand.	CRESTANIN	26.06.2026

Document no.		Projection method
SED 13117242 000 00	Scale	
Change no.	1:20	
1143366		

(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DRIVE ON WALL
OPTIONS:
070-1.12.201
070-1.12.202
070-1.12.202-2
070-1.12.210
DETC CONTROL

(2) BEVEL GEAR ON COVER
OPTIONS:
070-1.12.204

(3) BEVEL GEAR
OPTION:
070-1.12.203

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall


SERIAL NUMBER
–

MATERIAL NUMBER
101958710E


SHEET
1 / 1

A3

LAYOUT4B



LAYOUT4BI



(X) TRANSFORMER TANK COVER

(Y) TRANSFORMER SHORT TANK SIDEWALL

(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DRIVE ON WALL
OPTIONS:
070-1.12.201
070-1.12.202
070-1.12.202-2
070-1.12.210
DETC CONTROL

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) BEVEL GEAR ON COVER
OPTION:
070-1.12.204

(4) BEVEL GEAR
OPTION:
070-1.12.203

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13118267 000 00		
Chkd.	25.06.2026	MONDINN	Change no.	Scale	1:20
Stand.	26.06.2026	CRESTANIN	1143366		

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–


MATERIAL NUMBER
101958720E

SHEET
1 / 1

A3


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.

LAYOUT4C



View B

LAYOUT4CI



View A

(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DRIVE ON WALL
OPTIONS:
070-1.12.201
070-1.12.202
070-1.12.202-2
070-1.12.210
DETC CONTROL

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) BEVEL GEAR ON COVER
OPTION:
070-1.12.204

(4) BEVEL GEAR
OPTION:
070-1.12.203

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13148809 000 00		
Chkd.	25.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	1:20	

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–


MATERIAL NUMBER
101958730E

SHEET
1 / 1

A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.


LAYOUT5A




A

View A

LAYOUT5AI



A

View A 

(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DRIVE ON WALL
OPTIONS:
070-1.12.201
070-1.12.202
070-1.12.202-2
070-1.12.210
DETC CONTROL

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) CONICAL PLUG-IN COUPLING
OPTION:
070-1.12.211

(4) BEVEL GEAR ON WALL
OPTION:
070-1.12.204

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13112285 000 00	Scale 1:20	
Chkd.	25.06.2026	MONDINN	Change no. 1143366		
Stand.	26.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER –


MATERIAL NUMBER 101958740E

SHEET 1 / 1

A3


Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

LAYOUT5B




View A

LAYOUT5BI



View A



(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DRIVE ON WALL
OPTIONS:
070-1.12.201
070-1.12.202
070-1.12.202-2
070-1.12.210
DETC CONTROL

(2) BEVEL GEAR ON TAP-CHANGER
OPTIONS:
070-1.12.106

(3) CONICAL PLUG-IN COUPLING
OPTION:
070-1.12.211

(4) BEVEL GEAR ON WALL
OPTION:
070-1.12.204

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13148713 000 00	Scale 1:20	
Chkd.	25.06.2026	MONDINN	Change no. 1143366		
Stand.	25.06.2026	CRESTANIN			

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–


MATERIAL NUMBER 101958750E

SHEET 1 / 1


A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.

LAYOUT5C



LAYOUT5CI



	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13116584 000 00	Scale 1:20	
Chkd.	25.06.2026	MONDINN	Change no. 1143366		
Stand.	26.06.2026	CRESTANIN			

(X) TRANSFORMER TANK COVER
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DRIVE ON WALL
OPTIONS:
070-1.12.201
070-1.12.202
070-1.12.202-2
070-1.12.210
DETC CONTROL

(2) CONICAL PLUG-IN COUPLING
OPTIONS:
070-1.12.211

(3) BEVEL GEAR ON WALL
OPTION:
070-1.12.204

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall

SERIAL NUMBER
–


MATERIAL NUMBER 101958760E

SHEET 1 / 1


A3

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages.
All rights reserved in the event of the grant of a patent, utility model or design.

LAYOUT5D



LAYOUT5DI



	Date	Name	Document no.		Projection method
Dftr.	25.06.2026	CRESTANIN	SED 13133632 000 00	Scale 1:20	
Chkd.	25.06.2026	MONDINN	Change no. 1143366		
Stand.	25.06.2026	CRESTANIN			

(W) TRANSFORMER TANK BOTTOM
(Y) TRANSFORMER SHORT TANK SIDEWALL
(Z) TRANSFORMER LONG TANK SIDEWALL

(1) DRIVE ON WALL
OPTIONS:
070-1.12.201
070-1.12.202
070-1.12.202-2
070-1.12.210
DETC CONTROL

(2) CONICAL PLUG-IN COUPLING
OPTIONS:
070-1.12.211

(3) BEVEL GEAR ON WALL
OPTION:
070-1.12.205

ROTATION DIRECTION OF THE HAND WHEEL

MOVEMENT DIRECTION OF THE MOVING CONTACTS

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Assembly layout with drive on transformer wall


SERIAL NUMBER
–

MATERIAL NUMBER
101958770E


SHEET
1 / 1

A3


LAYOUT4A
LAYOUT4AI
LAYOUT4B
LAYOUT4BI
LAYOUT4C
LAYOUT4CI




LAYOUT5A
LAYOUT5AI
LAYOUT5B
LAYOUT5BI
LAYOUT5C
LAYOUT5CI



LAYOUT5D
LAYOUT5DI





(1) PROTECTIVE TUBE Φ85 mm

(2) PROTECTIVE TUBE Φ80 mm

(3) HOSE CLIPS

Telescopic protective tube supplied only upon request for manual drives.
Always included with the installation of the DETC CONTROL drive.

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 13128505 000 00		
Chkd.	19.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	1:10	

DIMENSION IN mm EXCEPT AS NOTED

MR

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Telescopic protective tube for drive shafts

SERIAL NUMBER
–

MATERIAL NUMBER
101958780E

SHEET
1 / 1

A3

LAYOUT TYPE	Dimensions (mm)			
	L Min.	LA Min.	LO Min.	LV Min.
1A – 1AI	210	–	–	–
1B – 1BI	220	–	–	–
2A – 2AI	–	394	–	–
2B – 2BI	–	383	–	–
2C – 2CI	–	394	–	–
2D – 2DI	–	414	–	–
2E – 2EI	–	394	–	–
3C – 3CI	–	383	–	–
3D – 3DI	–	403	–	–
4A –4AI	210	–	404	305
4B –4BI	220	–	404	305
4C – 4CI	–	–	404	305
5A – 5AI	–	–	–	335
5B – 5BI	–	–	–	335
5C – 5CI	–	383	–	335
5D – 5DI	–	403	–	335

- The dimensions reported in this table are the minimum mechanical dimensions achievable.
- The LA dimension for layouts not reported in this table depends on the tap-changer configuration.

Reinhausen GmbH Copyright reserved
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization ist prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

	Date	Name	Document no.		Projection method
Dftr.	16.06.2026	CRESTANIN	SED 13174233 000 00		
Chkd.	23.06.2026	MONDINN	Change no.	Scale	
Stand.	25.06.2026	CRESTANIN	1143366	-	

DIMENSION IN mm EXCEPT AS NOTED

DE-ENERGIZED TAP-CHANGER CAPT® 040+
Drive shaft lengths

SERIAL NUMBER
–
MATERIAL NUMBER 101958790E
SHEET 1 / 1
A3

Reinhausen GmbH
Falkensteinstrasse 8
93059 Regensburg
Germany
+49 941 4090-0
info@reinhausen.com
reinhausen.com

Please note:
The data in our publications may differ from the data of the devices delivered.
We reserve the right to make changes without notice.
13686366/00 EN - CAPT® 040+ Technical data -
F0446100 - 10/26
Reinhausen GmbH 2026

THE POWER BEHIND POWER.